

## TECHNICAL DATA

# Fluke CXT280 Extreme Case



## Key features

- Dimensions: 27.9 by 31.8 by 12.7 cm (11 by 12.5 by 5-Inch)
- Buoyancy allows case to float in salt water with 3.6 kg (7.94 lb) load
- Includes an automatic purge valve for quick equalization after changes in atmospheric pressure
- Features an exclusive 6.4 mm (0.25 in) neoprene O-ring and ABS latches for excellent seal

## Product overview: Fluke CXT280 Extreme Case

Unbreakable, watertight, airtight, dustproof, chemical resistant and corrosion proof case.

## Ordering information



### **Fluke-CXT280**

Fluke CXT280 Extreme Case

---

For use with the following test tools:

- Multimeters: 287, 289
- Earth Ground Testers: 1621

Fluke. *Keeping your world up and running.*®

**Fluke Europe B.V.**

P.O. Box 1186  
5602 BD Eindhoven  
The Netherlands  
[www.fluke.com/en](http://www.fluke.com/en)

©2024 Fluke Corporation. All rights reserved.  
Data subject to alteration without notice.  
07/2024

**For more information call:**

In Middle East/Africa  
+31 (0)40 267 5100

**Modification of this document is not permitted  
without written permission from Fluke Corporation.**