

Mobile Leeb Hardness Tester SAUTER HMO



Advanced features for professional applications

Features	Technical data	Accessories
<ul style="list-style-type: none"> Innovative touchscreen Automatic recognition of the impact (rebound) sensor connected to the SAUTER HMO Mobility: In comparison with stationary table-top devices and testing devices with an internal sensor, using the SAUTER HMO offers the highest level of mobility and flexibility All measurement directions possible (360°) by defining the direction of impact on the device USB socket for connection to the printer and charging the batteries 1 Hardness test block for calibration included Internal data memory for up to 500 values Mini statistics function: Displays the measure value, the average value, the difference between the maximum and minimum values, date and time Measurement value display: (B & C), Vickers (HV), Brinell (HB), Leeb (HL), tensile strength (MPa) Automatic unit conversion: The measuring result is automatically converted into all specified hardness units 2 Delivered in a robust carrying case 	<ul style="list-style-type: none"> Precision: $\pm 1\%$ at 800 HLD (± 6 HLD) Measuring range tensile strength: 375–2639 MPa (steel) Minimum sample weight on a solid and stable support: Sensor D + DC: 2 kg with fixed coupling Minimum sample material thickness: Sensor D + DC: 3 mm with coupling on fixed base Minimum sample radius (concave/convex): 50 mm (with support ring: 10 mm) Overall dimensions W×D×H 24×83×135 mm Internal rechargeable battery pack, operating time up to 50 h without backlight, charging time approx. 8 h, standard Mains adapter included Net weight approx. 4,6 kg 	<ul style="list-style-type: none"> External impact sensor Type D, as standard, can be reordered, SAUTER AHMO D 3 External impact sensor Type DC. Short impact sensor for tests in holes or hollowed objects, SAUTER AHMO DC On request: Support rings for bended test objects, SAUTER AHMR 01 4 Impact body Type D, net weight approx. 0,05 kg, hardness ≥ 1600 HV, tungsten carbide, impact ball $\varnothing 3$ mm, in accordance with standard ASTM A956-02, SAUTER AHMO D01 Connection cable impact sensor, SAUTER HMO-A04 Test block Type D/DC, $\varnothing 90$ mm (± 1 mm), net weight < 3 kg, hardness range 790 ± 40 HL, SAUTER AHMO D02 630 ± 40 HL, SAUTER AHMO D03 530 ± 40 HL, SAUTER AHMO D04 Paper roll, 1 piece, SAUTER ATU-US11 Factory calibration certificates for SAUTER AHMO D02, AHMO D03, AHMO D04, SAUTER 961-132

STANDARD										OPTION

Model	Sensor	Measuring range	Readout	Option
SAUTER		HL	[d] HL	Factory calibration certificate
HMO	D	170 – 960	1	KERN 961-131

<p>Adjusting program (CAL) For quick setting of the instrument's accuracy. External adjusting weight required</p>	<p>Bluetooth* data interface To transfer data from the balance/measuring instrument to a printer, PC or other peripherals</p>	<p>Measuring units Weighing units can be switched to e.g. non-metric. Please refer to website for more details</p>	<p>Conformity assessment Models with type approval for construction of verifiable systems</p>
<p>Calibration block Standard for adjusting or correcting the measuring device</p>	<p>WIFI data interface To transfer data from the balance/measuring instrument to a printer, PC or other peripherals</p>	<p>Measuring with tolerance range (limit-setting function) Upper and lower limiting can be programmed individually. The process is supported by an audible or visual signal, see the relevant model</p>	<p>DAkkS calibration possible The time required for DAkkS calibration is shown in days in the pictogram</p>
<p>Peak hold function Capturing a peak value within a measuring process</p>	<p>Data interface infrared To transfer data from the measuring instrument to a printer, PC or other peripheral devices</p>	<p>Protection against dust and water splashes IPxx The type of protection is shown in the pictogram cf. DIN EN 60529:2000-09, IEC 60529:1989 +A1:1999+A2:2013</p>	<p>Factory calibration (ISO) The time required for factory calibration is specified in the pictogram</p>
<p>Scan mode Continuous capture and display of measurements</p>	<p>Control outputs (optocoupler, digital I/O) To connect relays, signal lamps, valves, etc.</p>	<p>ZERO Resets the display to "0"</p>	<p>Package shipment The time required for internal shipping preparations is shown in days in the pictogram</p>
<p>Push and Pull The measuring device can capture tension and compression forces</p>	<p>Analogue interface To connect a suitable peripheral device for analogue processing of the measurements</p>	<p>Battery operation Ready for battery operation. The battery type is specified for each device</p>	<p>Pallet shipment The time required for internal shipping preparations is shown in days in the pictogram</p>
<p>Length measurement Captures the geometric dimensions of a test object or the movement during a test process</p>	<p>Analogue output For output of an electrical signal depending on the load (e.g. voltage 0 V - 10 V or current 4 mA - 20 mA)</p>	<p>Plug-in power supply 230V/50Hz in standard version for EU. On request GB, AUS or US version available</p>	
<p>Focus function Increases the measuring accuracy of a device within a defined measuring range</p>	<p>Statistics Using the saved values, the device calculates statistical data, such as average value, standard deviation etc.</p>	<p>Integrated power supply unit Integrated, 230V/50Hz in EU. More standards e.g. GB, AUS or US on request</p>	
<p>Internal memory To save measurements in the device memory</p>	<p>PC Software To transfer the measurement data from the device to a PC</p>	<p>Motorised drive The mechanical movement is carried out by an electric motor</p>	
<p>Data interface RS-232 Bidirectional, for connection of printer and PC</p>	<p>Printer A printer can be connected to the device to print out the measurement data</p>	<p>Motorised drive The mechanical movement is carried out by a synchronous motor (stepper)</p>	
<p>Profibus For transmitting data, e.g. between scales, measuring cells, controllers and peripheral devices over long distances. Suitable for safe, fast, fault-tolerant data transmission. Less susceptible to magnetic interference</p>	<p>Network interface For connecting the scale/measuring instrument to an Ethernet network</p>	<p>Fast-Move The total length of travel can be covered by a single lever movement</p>	
<p>Profinet Enables efficient data exchange between decentralised peripheral devices (balances, measuring cells, measuring instruments etc.) and a control unit (controller). Especially advantageous when exchanging complex measured values, device, diagnostic and process information. Savings potential through shorter commissioning times and device integration possible</p>	<p>KERN Communication Protocol (KCP) It is a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems</p>		
<p>Data interface USB To connect the measuring instrument to a printer, PC or other peripheral devices</p>	<p>GLP/ISO record keeping of measurement data with date, time and serial number. Only with SAUTER printers</p>		

*The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by KERN & SOHN GmbH is under license. Other trademarks and trade names are those of their respective owners.