

Milliohm Meter

IP65



IP65



CE


4136 mΩ

Power Source : 110V AC or 230V AC


FEATURES

- Protection class: IP65 (Lid closed)
- Microprocessor-controlled
- Four terminal measurement
- Five measuring ranges from 200.0mΩ to 2000Ω
- Maximum resolution of 100μΩ
- Three test currents with over-temperature protection
- Protection against inadvertent connection to over voltage
- Large LCD
- Potential lead resistance and current lead resistance checks
- "Full-featured" Ener-Save™ inside
- Ener-Save™ Auto hold
- Ener-Save™ Auto off
- Lightweight, robust & compact
- Indicators show if reading may be invalid (R_p , R_c , and temperature)
- "O-Ring" sealed case

4 Terminal Test




Simplified Measurement




Power Source : 12V DC

SPECIFICATIONS

Measuring ranges	0-200.0mΩ in steps of 100μΩ 0-2000mΩ in steps of 1mΩ 0-20.00Ω in steps of 10mΩ 0-200.0Ω in steps of 100mΩ 0-2000Ω in steps of 1Ω
Accuracy	±0.5% of reading ±2digits over the operating temperature range, -15°C ~ 55°C, with the supplied test leads
Test current	1mA=>2000Ω range 10mA=>200Ω and 20Ω ranges 100mA=>2000mΩ and 200mΩ ranges
Test current accuracy	±0.1%
Protection fuses	Mains = 500mA / 250V, 5 × 20mm fast blow Current = 500mA / 250V, 5 × 20mm fast blow Voltage = 500mA / 250V, 5 × 20mm fast blow
Maximum output voltage (C1~C2)	20V
Dimensions	250(L) × 190(W) × 110(D)mm
Weight	4136 mΩ: 1530g 4137 mΩ: 1500g
Safety standard	EN 61010-1 CAT IV 20V EN 61326-1
Accessories	Instruction manual Test leads Shoulder belt Batteries 1.5V(AA) × 8 (4137 mΩ)



AL-34B

TEL-4136C B
(optional)