



Revolving stage with glass plate



Illumination unit

## Professional Line MET

### The fully-equipped reflected and transmitted light microscope for numerous applications in metallurgy

#### Features

- This device is a professional, versatile, metallurgical microscope, which is used in testing metals and analysing surfaces
- The KERN OKO 178 is a combi variant of LED incident illumination and LED transmitted illumination. A height-adjustable 1.25 Abbe condenser which can be centred as well as a field diaphragm for complete professional Köhler illumination are part of the standard version.
- An open, mechanical angle table is integrated as standard
- A simple polarising unit (analyser and polariser) is included with delivery
- A large selection of accessories, such as, for example, eyepieces and further objectives are available for longer working distances
- A protective dust cover, eye cups, as well as multi-lingual user instructions are included in the scope of delivery
- A C-Mount adapter is required to connect a camera. You can select this adapter from the following model outfit list
- Please find detailed information in the following model outfit list

#### Scope of application

- Metallurgy, material testing, quality assurance

#### Applications/Samples

- Opaque and thick samples, workpieces (surfaces, fold lines, coatings)

#### Technical data

- Infinity optical system
- Quintuple nosepiece
- Siedentopf 30° inclined/360° rotatable
- Diopter adjustment: Both-sided
- Overall dimensions W×D×H 550×200×460 mm
- Net weight basic configuration approx. 14,5 kg

#### STANDARD



#### Model

Standard configuration

KERN	Tube	Eyepiece	Objective quality	Objectives	Illumination
OKO 178	Trinocular	HWF 10×/∅ 22 mm	Infinity Plan	5×/10×/20×/50×	5 W LED (incident + transmitted)

Model outfit		Model KERN	Order number
		OKO 178	
<b>Eyepieces</b> (30 mm)	HWF 10×/∅ 22 mm (adjustable)	✓	OBB-A1491
	HWF 10×/∅ 22 mm (reticule 0,1 mm) (adjustable)	✓	OBB-A1523
<b>Infinity Plan Semi Apochromatic objectives</b> for long working distance	5×/0,15 W.D. 21,0 mm	✓	OBB-A1619
	10×/0,3 W.D. 20,0 mm	✓	OBB-A1620
	20×/0,40 W.D. 15,0 mm	✓	OBB-A1621
	50×/0,75 W.D. 4,25 mm	✓	OBB-A1641
	100×/0,85 (dry) W.D. 3,00 mm	○	OBB-A1623
<b>Infinity Plan objectives</b> for long working distance	80×/0,80 (spring-loaded) W.D. 0,85 mm	○	OBB-A1530
<b>Trinocular tube</b>	<ul style="list-style-type: none"> <li>• Siedentopf 30° inclined/360° rotatable</li> <li>• Interpupillary distance 48 – 76 mm</li> <li>• Light distribution 100:0</li> </ul>	✓	
<b>Mechanical stage</b> for transmitted illumination	<ul style="list-style-type: none"> <li>• Stage size W×D 182×140 mm</li> <li>• Travel 77×52 mm</li> <li>• Coaxial coarse and fine focusing knobs</li> </ul>	✓	
<b>Reflected illumination unit</b>	Polarising unit (Incl. analyser, polariser and blue filter slide)	✓	
<b>Condenser</b>	Abbe N.A. 1,25 (aperture diaphragm)	✓	OBB-A1380
<b>Koehler illumination</b>	5 W LED spare bulb (transmitted)	✓	OBB-A1589
<b>Illumination polarising unit</b>	5 W LED spare bulb (incident)	✓	OBB-A1470
<b>Polariser</b>	For transmitted illumination	✓	OBB-A1470
<b>Colour filters</b> for transmitted illumination	Blue	✓	OBB-A1170
	Green	○	OBB-A1188
	Yellow	○	OBB-A1165
	Grey	○	OBB-A1183
<b>C-Mount</b>	1×	○	OBB-A1514
	0,75×	○	OBB-A1590
	0,5× (focus adjustable)	○	OBB-A1515

✓ = Included with delivery

○ = Option